

Quality ■
Tradition ■
Reliability ■



SIP

SPIDER 1500T TEDDERS



Easy folding for transport and storage.



Combined drawbar for upper or lower hitch. Stable, easy-to-use parking stand.



Gearbox with innovative protection system for both sides of the tedder.



Hydraulically adjusted working height (SIP patent). Rotor angle adjustment from 10° to 19°.



SIP

Your Partner on the Farm



Interlocked cast steel fingers fold trough 180° for reliable work and smooth run.



In spite of huge working with, very agile.



Due to unique hydraulic folding system, quick and easy preparation for transport.



Innovative construction and small rotor diameter, guarantee for best adaptation to the ground.

SPIDER Tedder	1500T
Number of rotors	14
No. of spring tines per rotor	6
Maximum capacity [ha/h]	15
Working width [m]	14,8
Transport width [m]	2,98
Transport height [m]	2,41
Machine width [m]	15
Weight [kg]	2950
Required tractor power [kW]	70
PTO [rpm]	540
Tyres	16x6.50-8
Safety clutch [Nm]	2x1500



Encapsulated, permanently lubricated gearboxes are identical and propelled by hexagonal shaft.

For further information please contact:

SIP Strojna Industrija d.d.
Juhartova ulica 2, SI-3311 Šempeter v Sav. dolini
Slovenia
Tel.: +386 3 703-85-00
Fax: +386 3 703-86-63
E-mail: info@sip.si



ISO 9001:2008
Management Service

www.sip.si